Petrolatum Primer MP



- GUARDIAN Petrolatum Primer MP is a key component of the GUARDIAN Splash-zone Systems.
- GUARDIAN Petrolatum Primer MP is a Petrolatum Compound incorporating inert fillers, water repellant agents, water displacement agent, wide spectrum biocides and corrosion inhibitors.
- GUARDIAN Petrolatum Primer MP is inert, stable in nature, GUARDIAN **Petrolatum Primer** maintains its plasticity over a wide temperature range.
- GUARDIAN Petrolatum Primer profiles minor surface imperfections and enables uniform application of GUARDIAN Petrolatum Tape MT and GUARDIAN Splash-zone 60GW, 100 & 2000 Series.

PROPERTIES

Property	Test Method	Value		
Flash Point		180°C		
Specific Gravity	ASTM D70 @ 25°C (Mod)	1.1 (Average)		
Drop Melting Point	ASTM D127 (Mod)	75°C		
Petrolatum Content		75% Min. by Weight		
Coverage*		1 to 2m2/kg (Average)		
*Note that coverage is determined by surface profile.				
Heavily pitted substrates will require more primer compared to a smooth surface substrate.				
Application Temperatures	-10 to +50°C			
Service Temperature	-10 to +75°C			
Service Life	20 Years +			
Shelf Life	20 Years +			

PACKAGING

Part No.	Weight	Unit	Carton Qty
PP04MP	4kg	Tub	2 Tubs/Carton
PP20MP	20kg	Drum	1 Drum

All statements and data presented herein are given in good faith and believed to be appropriate and reliable. It is given without express or implied warrant or guarantee.

Potential users of Guardian's materials are urged to conduct confirmatory trials to satisfy themselves as

to the suitability of the selected product for their particular end use prior to purchase.

BENEFITS

Isolates marine pile from the environment Salt and seawater resistant Contains water repellant and displacing agents

APPLICATION

Refer to the relevant GUARDIAN System Application Data Sheet

