

Multi Environment Corrosion Protection System

- **GUARDIAN Petrolatum Primer** is a key component of the GUARDIAN Petrolatum ST & HT Systems.
- **GUARDIAN Petrolatum Primer** is a Petrolatum Compound incorporating inert fillers and corrosion inhibitors.
- **GUARDIAN Petrolatum Primer** is manufactured in accordance with AWWA Standard C217-14
- **GUARDIAN Petrolatum Primer** is inert, stable in nature, **GUARDIAN Petrolatum Primer** maintains its plasticity over a wide temperature range.
- **GUARDIAN Petrolatum Primer** profiles minor surface imperfections and enables uniform application of **GUARDIAN Petrolatum Mastic HT** and **GUARDIAN Petrolatum Tape ST & HT** to a Class St2 clean substrate.

PROPERTIES

Property	Test Method	Value
Flash Point	ASTM D92	180°C
Specific Gravity	ASTM D70 @ 25°C (Mod)	1.1 (Average)
Drop Melting Point	ASTM D127 (Mod)	55°C
Cone Penetration at 25°C, 100g wt, 5 sec;mm	ASTM D937 (Mod)	15mm (Average)
Petrolatum Content		75% Min by Weight
Coverage		5m ² /kg (Average)
Application Temperatures	-10 to + 50°C	
Service Temperatures	-10 to + 75°C	
Service Life	30 Years +	
Shelf Life	30 Years +	

PACKAGING

Part No.	Weight	Unit	Carton Qty
FG000568	4kg	Tub	2 Drums
FG000569	20kg	Drum	1 Drum

APPLICATION

Refer to the GUARDIAN Petrolatum System: Application Data Sheet.

All statements and data presented herein are given in good faith and believed to be appropriate and reliable. It is given without express or implied warrant or guarantee. Potential users of Guardian's materials are urged to conduct confirmatory trials to satisfy themselves as to the suitability of the selected product for their particular end use prior to purchase.